

Sheet 1 of 2

Product: Freestanding Depository with Safe

Catalog#: 04-9830

Date of revision: March 29, 2014. Go to <a href="https://www.kingsley.com">www.kingsley.com</a> for all updates. Specifications are subject to change without notice. MADE IN THE USA

## ACCESSORIES/OPTIONS FOR THIS SYSTEM

Custom Wording/Graphics or Finish (Call for quote)

## **CONSTRUCTION**

Construction Materials: Cabinet: .080 aluminum.

Hood, Access Door and Bottom: .080 Aluminum

Faceplate: The faceplate, weather shroud, depository opening and envelope dispenser door are made from Stainless Steel and

aluminum.

Inside Support Base: Three piece heavy duty galvanized

steel.

Chute: Galvanized

Construction Methods: Cabinet: One piece of Aluminum forms all four corners of the

cabinet.

Access Door Header: Welded in place

Hood: One-piece top, sides, and rear. Faceplate welded in

place. Fully sealed to prevent leaking. **Bottom**: Full aluminum welded to frame.

**Safe:** Constructed with solid steel to resist hand and mechanical tool tampering. Powder coated interior and exterior. Is mounted to the base with four heavy duty anchor bolts which go through to the cabinet bottom and into your

concrete pad.

## **FEATURES**

Weather Resistance: No corner seams to leak or pull apart in heavy winds or under

weight of snow. Sealed access door.

The depository opening is protected with a built in weather

shroud. Sloped and radius top to help shed water.

Safe: 2 cubic foot safe. Simple to operate electronic lock. Comes with

(2) override keys. Programmable to have many combinations.

**Envelope dispenser:** The Envelope Dispenser compartment with a sliding door is built

into the faceplate.

**Theft Deterrence:** The built in theft deterrent system makes removing articles

through the depository opening virtually impossible.

Fire Suppression: Air tight design smothers most fires in under 1 minute

Finish: Standard finishes with a Graffiti-X clear coat option. See website

for complete list.

## 04-9830 Freestanding Depository with Safe Continued

**Locking Method:** 3-point locking (top, bottom, opening side). Keyed paddle lock

with weather sealed lock cover to resist freezing and keep dirt

out.

**ADA Compliancy:** ADA Compliant when properly installed.

**Depository:** One hand Kwik drop depository with weather shroud.

**Assembly Required:** Ships fully assembled.

**DIMENSIONS** 

**Overall Dimensions:** 24"L x 37 1/8"W x 53 1/4"H [609.6mmL x 942.9mmW x 1352.5mmH]

**Depository Opening:** 10"W x ½"H [25.4mmW x 12.7mmH]

**Product Weight:** 138 lbs. [62.60 kg]

Shipping Method/Class: LTL/Class 150