

Thru-Wall Depositories

Product: ValuStar

Catalog#: 10-9116

Specifications are subject to change without notice. Please see www.kingsley.com for the most current specifications. **Made in the USA.**

Thru-Wall System Construction/Features

Materials:	<ul style="list-style-type: none">• Exterior: Aircraft grade corrosion resistant aluminum construction.• Interior: Aircraft grade corrosion resistant aluminum and the AirBloc is constructed from neoprene rubber.
Weather Resistance:	Depository door is gravity and weight balanced to prevent the entry of rain or snow and stays closed in most winds.
Air Draft Prevention	The optional AirBloc system helps to eliminate drafts caused when the depository door is opened. It helps stabilize outside air temperature before it enters the building.
Theft Deterrence:	This unit design includes anti-phishing features. For example, an upward depository angle and long retrieval distances prevents someone from reaching inside and pulling materials out. We test all our units to make sure that nothing can be retrieved.
Available Wording:	Vinyl decal, silkscreen, and routing available. See website for complete list of standard wording options.
Locking Method:	Depository flap locking system. Simply push on the slide towards the door and the slide will move into place blocking the flap door locking it into place.
ADA Compliancy:	ADA compliant when properly installed.
Assembly Required:	The ValuStar Thru-Wall is a pre-assembled, one-piece unit so it is easy to install. The Thru-Wall was designed to fit in between 16 on center studs for quick and easy installation. The internal slide is a separate piece that must be hooked into place once the depository is installed. This allows the unit to be installed with appropriate hardware that would be normally blocked by the slide.

Compatibility: Contingent on height of installation, the ValuStar Thru-Wall return is compatible with any Kingsley receiving cart except for the divided DualDrop carts. It is also compatible with most conveyer systems.

ThruWall Measurements

Overall Dimensions:	13.8" D x 18.08" W x 12.23" H [350.5 mm D x 459.2 mm W x 310.6 mm H]
Depository Opening:	13" W x 2.7" H [330 mm W x 68.6 mm H]
Product Weight:	7.84 lbs. [3.55 kg]
Shipping Method/Class:	Ground or freight/class 150

Installation

(Rough cut only. Please visit www.kingsley.com for complete instructions)

Rough Cut:	38-7/8" [987.5 mm] from exterior floor to bottom of cut out. Rough cut opening 14-1/2" W x 10" H [368.3 mm W x 254 mm H] all the way through wall. Four-sided chute housing extends 13 inches from the faceplate and will cover the wall rough cuts when installed. For the quickest and easiest install, mount the Thru-Wall between 16 on center studs.
Trim:	1/4" [6.35 mm] trim on the top, bottom and sides of opening.

Accessories/Options for This System:

- Braille Tags** – Reads: BALLOT RETURN (#99-8115)
- Custom Vinyl Wording** – Contact us for a quote.